

# 3M ARMR220 Protection Film

Preliminary Data Sheet

April 2011

**Description** 3M™ ARMR220 Protection Film uses 3M's advanced coating technology to durable protection, reflection reduction for a clear image, with a residue-free, self-wetting adhesive for application on electronic displays.

**Applications** 3M ARMR220 Protection Film is typically used to provide display protection and viewing enhancement for electronic displays, especially in environments where bright light conditions can disrupt display readability.

The combination anti-reflection/anti-glare front surface enhances the viewing experience by reducing ambient light reflection on a display as well as diffusing mirror-like reflections. The film and coatings are near color-neutral and non-conductive, enabling application to any of today's touch panel technologies. By providing a durable hardcoat barrier between the display surface and the user or environment, this film helps protect against scratches and damage to the display. The residue-free adhesive technology gives an easy-to-apply and easy-to-remove application experience for the user.

## Typical Properties

Technical information provided consists of typical developmental product data and should not be used for specification purposes. Unless otherwise noted, all tests are performed at room temperature.

Property (Test Method)	Typical Value US units (metric)
% Transmission	≥ 93%
Haze	≤ 3%
Clarity	≥ 75%
Reflection	≤ 1.6%
Nominal thickness (with adhesive)	6 mil
Steel Wool Abrasion	Light scratching, 25 g/cm <sup>2</sup> , 10 rubs, #0000 steel wool
Pencil Hardness	≥ 3H
Water contact angle (hydrophobic)	≥ 95 degrees
Hexadecane contact angle (oleophobic)	≥ 35 degrees
Heat resistance	85 <sup>0</sup> C for 500 hours
Cold resistance	-40 <sup>0</sup> C for 500 hours
Humidity resistance	60 <sup>0</sup> C/90% RH for 500 hours
Thermal shock resistance	85 <sup>0</sup> C for 1 hour to -40 <sup>0</sup> C for 1 hour, 100 cycles
Chemical resistance	Bleach, MEK, IPA, Acetone, Window cleaner, motor oil, cola, coffee, water insoluble marker, water

# 3M ARMR220 Protection Film

## Product Features

- Durable hardcoat for display protection
- Non-conductive, near color-neutral Anti-Reflection surface treatment
- Anti-glare coating to reduce mirror-like reflections
- Low tack, easy to apply and remove adhesive
- Scotchgard™ easy-to-clean hydrophobic and oleophobic surface

---

## Shelf Life & Storage (prior to application)

Material should be stored in its original packaging, laying in a horizontal orientation, away from direct sunlight. Heavy objects should not be piled on top of it to avoid damaging the product. Ambient temperature and humidity should be controlled to 10-30° C at 30-60% relative humidity.

---

## Availability

For availability, please contact our customer service group at 1-800-553-9215 or visit our website at [3mprivacyfilter.com](http://3mprivacyfilter.com)

---

## Important Sample Notice

This prototype or product (the "Product") is developmental and made available to the recipient ("Recipient") on a non-exclusive basis for the sole purpose of evaluating its use in Recipient's application. Product may vary product-to-product and lot-to-lot or be changed in the future without notice. 3M does not guarantee future availability. Product is transferred subject to 3M's Standard Terms and Conditions, except as modified by this Notice. Products may be subject to patent applications and/or other intellectual property rights held by 3M or its designated affiliate (the "IP Rights") and no license of any IP Rights is granted to Recipient except for the limited purpose described above. In addition to any other confidentiality obligations that Recipient may have to 3M, for three years after the date of last shipment. Recipient shall treat each Products as 3M's confidential information using such care as Recipient uses in maintaining the confidentiality of its own secret information, but no less than a reasonable degree of care.

Recipient has the sole responsibility for determining if a Product is fit for Recipient's particular purposes, suitable for Recipient's production methods, and handled in a safe manner. THE PRODUCT IS BEING TRANSFERRED ON AN "AS IS, WHERE IS" BASIS. EXCEPT AS TO TITLE, 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT NLIMITED TO, (A) IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND ARISING OUT OF A COURSE OF DEALING, A CUSTOM OR USAGE OF TRADE; (B) A WARRANTY RELATING TO A PRODUCTS EFFECTIVE LIFE OR ABILITY TO SURVIVE ANY TESTING, OR (C) RESOLUTION OF ANY TECHNICAL ISSUES NECESSARTY TO DEVELOP A COMMERCIAL VERSION OF A PRODUCT. 3M WILL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE TO RECIPIENT FOR DIRECT, SPECIAL, INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT LIMITED TO, LOSS OF PROFITS) RESULTING FROM OR IN ANY WAY RELATED TO A PRODUCT OR THIS AGREEMENT. This limitation applies regardless of whether the damages or other relief are sought based on breach of warranty, breach of contract, negligence, strict liability in tort, or any other legal or equitable theory.

---

3M is a trademark of 3M Company

**3M**  
Mobile Interactive Solutions Division  
Bldg. 235-1E-54/3M Center  
St. Paul, MN 55144-1000  
800-553-9215  
[www.3mprivacyfilter.com](http://www.3mprivacyfilter.com)

Please recycle  
© 3M 2010 All rights reserved